

SAFETY DATA SHEET

Version 1

Issue Date 27-May-2015

Revision Date 27-May-2015

1. IDENTIFICATION

Product identifier

Product Name

CCA - C Heavy Duty™ Wood

Other means of identification

Product Code

20001

Synonyms

No information available

Recommended use of the chemical and restrictions on use

Recommended Use

Treated Wood.

Details of the supplier of the safety data sheet

Supplier Address

Manufacturer Address

Customers and Licensees of:

THUNDERBOLT WOOD TREATING

Arch Wood Protection, Inc.

3400 PATTERSON RD

360 Interstate North Parkway, Suite 450

RIVERBANK, CA. 95367

Atlanta, GA 30339

Emergency telephone number

Company Phone Number

209-869-4561

24 Hour Emergency Phone Number

800-654-6911

Emergency Telephone

209-869-4561

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|-------------|
| Skin corrosion/irritation | Category 3 |
| Serious eye damage/eye irritation | Category 2B |
| Respiratory sensitization | Category 1 |
| Skin sensitization | Category 1 |
| Carcinogenicity | Category 1A |
| Specific target organ toxicity (single exposure) | Category 3 |


Label elements

Emergency Overview

Danger

Hazard statements

- Causes eye irritation
- May cause allergy or asthma symptoms or breathing difficulties if inhaled
- May cause an allergic skin reaction
- May cause cancer
- May cause respiratory irritation
- Causes mild skin irritation



Physical state Solid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Avoid breathing dust/fume/gas/mist/vapors/spray
 In case of inadequate ventilation wear respiratory protection
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment (see first aid section on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Causes mild skin irritation Very toxic to aquatic life

Unknown acute toxicity

No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Synonyms

No information available.

| Chemical Name | CAS No. | Weight-% | Trade Secret |
|---------------------|--------------|----------|--------------|
| Wood and Wood Dust | NOT ASSIGNED | 90 - 100 | |
| Chromic Acid (CrO3) | 7738-94-5 | 0.1 - 1 | |
| Arsenic Acid | 7778-39-4 | 0.1 - 1 | |
| Cupric Oxide | 1317-38-0 | 0.1 - 1 | |

4. FIRST AID MEASURES

Description of first aid measures

| | |
|------------------------------------|---|
| General advice | If symptoms persist, call a physician. |
| Eye contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. |
| Skin contact | Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician. |
| Inhalation | Remove to fresh air. If not breathing, give artificial respiration. If symptoms persist, call a physician. |
| Ingestion | Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. |
| Self-protection of the first aider | Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. |

Most important symptoms and effects, both acute and delayed

Symptoms See Section 11: TOXICOLOGICAL INFORMATION.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Carbon dioxide (CO2). Water spray or fog.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

In the event of fire and/or explosion do not breathe fumes. May cause sensitization in susceptible persons. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Toxic gas. Nitrogen oxides (NOx).

Explosion data

Sensitivity to Mechanical Impact Warning.
Sensitivity to Static Discharge Warning.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12: ECOLOGICAL INFORMATION.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Cover powder spill with plastic sheet or tarp to minimize spreading.

Methods for cleaning up Use personal protective equipment as required. Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Take up mechanically, placing in appropriate containers for disposal. Avoid creating dust. Clean contaminated surface thoroughly. Pick up and transfer to properly labeled containers. Sweep up and shovel into suitable containers for disposal. After cleaning, flush away traces with water. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Do not burn treated wood. Do not use pressure treated chips or sawdust as mulch. Use with local exhaust ventilation. May form combustible dust concentrations in air. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Conditions Avoid generation of dust.

Incompatible materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---|---|--|--|
| Wood and Wood Dust NOT ASSIGNED | 1.0 mg/m ³ Inhalable, 0.5 mg/m ³ Inhalable Western Red Cedar | 15 mg/m ³ Total Dust 5.0 mg/m ³ Respirable Fraction | - |
| Chromic Acid (CrO ₃) 7738-94-5 | - | TWA: 5 µg/m ³ (vacated) Ceiling: 0.1 mg/m ³ Ceiling: 0.1 mg/m ³ CrO ₃ applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect | TWA: 0.0002 mg/m ³ Cr |
| Arsenic Acid 7778-39-4 | TWA: 0.01 mg/m ³ As | TWA: 10 µg/m ³ As | IDLH: 5 mg/m ³ As |
| Cupric Oxide 1317-38-0 | TWA: 1 mg/m ³ Cu dust and mist | - | Ceiling: 0.002 mg/m ³ As 15 min IDLH: 100 mg/m ³ Cu dust and mist TWA: 0.1 mg/m ³ Cu fume TWA: 1 mg/m ³ Cu dust and mist |

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations
 Ventilation systems. Ventilation: Saw, cut or machine wood outdoors or in well ventilated areas. Due to the explosive potential of dust when suspended in air, precautions should be taken when sawing, sanding, or machining wood or wood products to prevent sparks or other ignition sources. If required, use wet methods and/or explosion suppression systems to reduce generation of dust. Local exhaust ventilation is recommended when sawing, sanding, or machining this product. General dilution ventilation is recommended in processing and storage areas.

Individual protection measures, such as personal protective equipment

| | |
|--------------------------------|---|
| Eye/face protection | Use safety glasses with side shields or chemical goggles when sawing or cutting treated or untreated wood. |
| Skin and body protection | Wear leather gloves. Wear long sleeve shirt, pants, and steel-toed shoes when handling treated or untreated wood. |
| Respiratory protection | None normally required. When sawing or cutting treated or untreated wood, wear a NIOSH approved N95 or better dust mask. |
| General Hygiene Considerations | When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wash hands thoroughly after handling. Keep away from food, drink and animal feeding stuffs. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|----------------|--------------------------|----------------|--------------------------|
| Physical state | Solid | Odor | No information available |
| Appearance | No information available | Odor threshold | No information available |
| Color | Slightly green | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|--------------------------------|--------------------------|-------------------------|
| pH | No information available | |
| Melting point / freezing point | No information available | |
| Boiling point / boiling range | No information available | |
| Flash point | Not applicable | |
| Evaporation rate | No information available | |
| Flammability (solid, gas) | No information available | |
| Flammability Limit in Air | | |
| Upper flammability limit: | No information available | |
| Lower flammability limit: | No information available | |
| Vapor pressure | No information available | |
| Vapor density | No information available | |
| Relative density | No information available | |
| Water solubility | No information available | |
| Solubility in other solvents | No information available | |
| Partition coefficient | No information available | |
| Autoignition temperature | No information available | |
| Decomposition temperature | No information available | |
| Kinematic viscosity | No information available | |
| Dynamic viscosity | No information available | |
| Explosive properties | No information available | |
| Oxidizing properties | No information available | |

Other Information

| | |
|------------------|--------------------------|
| Softening point | No information available |
| Molecular weight | No information available |
| VOC Content (%) | No information available |
| Density | No information available |

Bulk density No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

| | |
|--------------|---|
| Inhalation | WOOD and WOOD DUST :. May cause cancer. May cause sensitization by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Eye contact | WOOD and WOOD DUST :. Irritating to eyes. |
| Skin contact | WOOD and WOOD DUST :. May cause irritation. May cause allergic skin reaction. |
| Ingestion | WOOD and WOOD DUST :. Harmful if swallowed. |

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|----------------------------------|-------------------------|-------------------------|-------------------|
| Chromic Acid (CrO3) 7738-94-5 | 80 mg/kg (Rat) | - | - |
| Arsenic Acid 7778-39-4 | = 141.4 mg/kg (Rat) | = 1,750 mg/kg Rat(m) | 0.794 mg/L Rat(m) |
| Cupric Oxide 1317-38-0 | >2,500 mg/kg LD50 (Rat) | >3,500 mg/kg LD50 (Rat) | - |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|------------------------------------|-------|---------|-------|------|
| Wood and Wood Dust NOT ASSIGNED | X | Group 1 | X | X |
| Chromic Acid (CrO3) 7738-94-5 | - | Group 1 | Known | X |
| Arsenic Acid 7778-39-4 | A1 | Group 1 | Known | X |

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity

Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. May cause adverse liver effects.

Target Organ Effects

Eyes, kidney, liver, lungs, Lymphatic System, Respiratory system, Skin.

Other adverse effects

Study Abstracts: In Hawaii, where over 45,000 homes have been built almost entirely of CCA-treated wood, a study was conducted by the Pacific Biomedical Center of the University of Hawaii (the Budy-Rashad study) in 1977 to determine any possible effect on the health of carpenters. The study concluded that exposure to CCA-treated sawdust is not associated with increased risk of total cancer, lung cancer or lymphatic cancer and shows that excess respiratory cancer mortality was not observed in the carpenters.

A study was conducted by the University of Alabama to evaluate the teratogenicity of CCA-impregnated sawdust when exposed to rabbits and mice. Sawdust from CCA-treated wood has been shown not to cause chromosome damage, or teratogenic effects in mice fed sawdust, nor to cause birth defects in rabbits, receiving sawdust applied to their skin. According to a Human Health Risk Assessment conducted by Gradient Corporation in August 2004, potential health risks to workers and residents do not exceed U.S. Environmental Protection Agency acceptable risk limits. Although the arsenic complex (the predominate chemical form of arsenic in CCA-treated wood is chromium III arsenate) is present on the surface of CCA-treated utility poles and in surrounding soils, the arsenic in these poles is chemically bonded to the wood and is not readily absorbed in the body. This risk assessment evaluated exposures to arsenic complex on the surface of CCA treated utility poles and in soil adjacent to the poles. Exposure was evaluated for both hand to mouth contact and skin contact for a child resident age 2-6 and an adult utility pole worker. The assessment results also indicate that the amount of arsenic complex potentially taken into the body from exposures to CCA-treated utility poles and adjacent soils for a child resident is approximately 8 fold less than the intake of naturally occurring inorganic arsenic in food and drinking water at the new federal drinking water standard for arsenic. An adult worker is exposed to over 24 fold less arsenic complex associated with CCA-treated utility poles, compared to intake of inorganic arsenic from food and drinking water.

Carcinogenic status: IARC, the NTP, OSHA and California Proposition 65 do not consistently distinguish among arsenic or chrome species but list inorganic arsenic and chromium and certain chromium compounds as human carcinogens. Cancers in humans have followed from long term consumption of Fowler's Solution, a medicinal trivalent arsenical; inhalations and skin contact with inorganic trivalent arsenical sheep-dust; the combined inhalation of arsenic trioxide (trivalent arsenical), sulfur dioxide, and other particulates from ore smelting in arsenic trioxide production; and occupational exposure to nonwater-soluble hexavalent chromium. Carcinogenicity Data: IARC has classified untreated hardwood and hardwood/softwood mix wood dust as a Group I human carcinogen. The wood dust classification is based primarily on IARC's evaluation of increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with occupational exposures to untreated wood dust. NTP has classified all untreated wood dust as a carcinogen.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document.

| | |
|-------------------------------|-------|
| ATEmix (oral) | mg/kg |
| ATEmix (dermal) | mg/kg |
| ATEmix (inhalation-gas) | |
| ATEmix (inhalation-dust/mist) | mg/l |
| ATEmix (inhalation-vapor) | |

Numerical measures of toxicity

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects

Study Abstracts: A technical paper published in the Forest Products Journal (September, 1974) by Levi, Huisingh and Nesbitt described a study conducted to determine if CCA wood preservative in grapevine support posts might be absorbed by the vines, leaves and/or grapes. This study concluded that "... CCA preservatives are bound in wood, are not readily leached and are not concentrated in plants growing close to the treated wood."

The Springborn Laboratories Environmental Sciences Division in 1993 conducted a sediment exposure study using leachate from CCA treated and untreated marine pilings and exposing *Ampelisca abdita* for a period of 10 days. Survival of the organisms during the 10-day exposure period was the biological endpoint used to establish the effects of exposure. Results indicated that leachate from treated pilings had no adverse effect on organism survival. It was concluded that the primary constituents of the CCA-treated wood piling were not present in the leachate at concentrations which would adversely affect the survival of the organisms.

Testing has been conducted to evaluate the use of treated wood in raised vegetable gardens. Vegetables harvested from gardens in raised bed structures built of CCA-treated wood were compared with vegetables grown in untreated raised bed structures and with vegetables purchased at a local grocery store. Testing revealed that all vegetables contained minuscule amounts of each element in CCA. In some cases, the levels of metals were actually higher in the vegetables grown in untreated bins, and in one case the store-purchased vegetable had the highest level of arsenic. The report concluded that there was "no uptake of the metal constituents into the vegetables."

The Food and Drug Administration's (FDA) "Market Basket Survey" has consistently shown that arsenic in tomatoes is below the analytical level of detection despite the increased usage of arsenically-treated wood for tomato stakes. Moreover, even though CCA-treated wood has been increasingly used in applications such as cattle bunks and stalls and poultry brooders for the last ten years, the FDA survey has shown a decrease in the arsenic content of dairy, meat and poultry products.

A study funded in part by the National Oceanic and Atmospheric Administration (NOAA) and prepared by the Marine Resources Division of the South Carolina Department of Natural Resources in 1995 measured the impact of wood preservative leachate from docks in an estuarine environment. Copper, chromium, arsenic, and polynuclear aromatic hydrocarbons (PAHs) were measured in composite samples of sediments and naturally occurring oyster populations from creeks with high densities of docks, and from nearby reference creeks with no docks. Sediments from all but one site had metal and total PAH concentrations which were below levels reported to cause biological effects, and the oysters showed no significant difference in their physiological condition.

Bioassays were also conducted on four common estuarine species and hatchery-reared oysters. The results suggest that wood preservative leachates from dock pilings have no acutely toxic effects on these common species, nor do they affect the survival or growth of juvenile oysters over a six-week period. In some cases, metal leachates may accumulate in sediments and oysters immediately adjacent to pilings, but do not appear to become concentrated in sediments or oysters elsewhere in the same creeks.

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects

No information available

| |
|------------------------------------|
| 13. DISPOSAL CONSIDERATIONS |
|------------------------------------|

Waste treatment methodsDisposal of wastes

DO NOT BURN TREATED WOOD. Do not use pressure treated chips or sawdust as mulch. Dispose of in accordance with local, state and federal regulations. This product is exempted as a hazardous waste under any sections of the RCRA regulations as long as the product is being utilized for its intended end use as stated in 40 CFR 261.4 (b) (9). State run hazardous waste programs may be more stringent.

Contaminated packaging

No information available.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|----------------------------------|-----------------------------------|
| Chromic Acid (CrO3) 7738-94-5 | Toxic Corrosive Ignitable |
| Cupric Oxide 1317-38-0 | Toxic |

14. TRANSPORT INFORMATION

| | |
|-------------------|---------------|
| <u>DOT</u> | Not regulated |
| <u>TDG</u> | Not regulated |
| <u>MEX</u> | Not regulated |
| <u>ICAO (air)</u> | Not regulated |
| <u>IATA</u> | Not regulated |
| <u>IMDG</u> | Not regulated |
| <u>RID</u> | Not regulated |
| <u>ADR</u> | Not regulated |
| <u>ADN</u> | Not regulated |

15. REGULATORY INFORMATION

International Inventories

| | |
|---------------|-----------------|
| TSCA | Does not comply |
| DSL/NDSL | Does not comply |
| EINECS/ELINCS | Does not comply |
| ENCS | Does not comply |
| IECSC | Does not comply |
| KECL | Does not comply |
| PICCS | Does not comply |
| AICS | Does not comply |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % |
|---------------------------------|-------------------------------|
| Chromic Acid (CrO3) - 7738-94-5 | 0.1 |
| Arsenic Acid - 7778-39-4 | 0.1 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute health hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire hazard | Yes |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|----------------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Chromic Acid (CrO3) 7738-94-5 | 10 lb | X | - | - |
| Arsenic Acid 7778-39-4 | - | X | - | - |
| Cupric Oxide 1317-38-0 | - | X | - | - |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|----------------------------------|--------------------------|----------------|--|
| Chromic Acid (CrO3) 7738-94-5 | 10 lb | - | RQ 10 lb final RQ RQ 4.54 kg final RQ |
| Arsenic Acid 7778-39-4 | 1 lb | - | RQ 1 lb final RQ RQ 0.454 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 |
|-----------------------------------|---|
| Wood and Wood Dust - NOT ASSIGNED | Carcinogen |
| Chromic Acid (CrO3) - 7738-94-5 | Carcinogen Developmental Female Reproductive Male Reproductive |
| Arsenic Acid - 7778-39-4 | Carcinogen |
| Lead - impurity - 7439-92-1 | Carcinogen Developmental Female Reproductive Male Reproductive |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|----------------------------------|------------|---------------|--------------|
| Water 7732-18-5 | - | - | X |
| Chromic Acid (CrO3) 7738-94-5 | X | X | X |
| Arsenic Acid 7778-39-4 | X | X | X |
| Cupric Oxide 1317-38-0 | X | - | X |
| Lead - impurity 7439-92-1 | X | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number N/A

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

| | | | | |
|-------------|------------------|----------------|--------------------|------------------------------------|
| <u>NFPA</u> | Health hazards 2 | Flammability 1 | Instability 0 | Physical and Chemical Properties - |
| <u>HMIS</u> | Health hazards 2 | Flammability 1 | Physical hazards 0 | Personal protection X |

Issue Date 27-May-2015

Revision Date 27-May-2015

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Warning - Potential Danger

These products are treated with wood preservatives registered with the United States Environmental Protection Agency and the California Department of Pesticide Regulation and should only be used in compliance with the product labels.

This wood may contain chemicals classified by the State of California as hazardous and should be handled and disposed of with care. Check product label for specific preservative information and Proposition 65 warnings concerning presence of chemicals known to the State of California to cause cancer or birth defects.

Anyone working with treated wood, and anyone removing old treated wood, needs to take precautions to minimize exposure to themselves, children, pets, or wildlife, including:

- ◆ Avoid contact with skin. Wear gloves and long sleeved shirts when working with treated wood. Wash exposed areas thoroughly with mild soap and water after working with treated wood.

- ◆ Wear a dust mask when machining any wood to reduce the inhalation of wood dusts. Avoid frequent or prolonged inhalation of sawdust from treated wood. Machining operations should be performed outdoors whenever possible to avoid indoor

- ◆ Wear appropriate eye protection to reduce the potential for eye injury from wood particles and flying debris during machining.
- ◆ If preservative or sawdust accumulates on clothes, launder before reuse. Wash work clothes separately from other household clothing.
- ◆ Promptly clean up and remove all sawdust and scraps and dispose of appropriately.
- ◆ Do not use treated wood under circumstances where the preservative may become a component of food or animal feed.
- ◆ Only use treated wood that's visibly clean and free from surface residue for patios, decks, walkways.
- ◆ Do not use treated wood where it may come in direct or indirect contact with public drinking water, except for uses involving incidental contact such as docks and bridges.
- ◆ Do not use treated wood for mulch.
- ◆ Do not burn treated wood. Preserved wood should not be burned in open fires, stoves, or fireplaces.

**For further information, go to www.WWPIInstitute.org
or call 1-866-696-8315**

Attention Retailers and Wholesalers of Treated Wood
Products in California.

In 2004 California Assembly Bill 1353 modified the Health and Safety Code adding section 25150.7 dealing with the disposal of treated wood. The bill requires effective January 1, 2005, that:

"Each wholesaler and retailer of treated wood and treated wood-like products in this state shall conspicuously post information at or near the point of display or customer selection of treated wood and treated wood-like products used for fencing, decking, retaining walls, landscaping, outdoor structures and similar uses." [(AB 1353 Section 1(f)(1))]

In accordance with provisions of the act the warning statement on the composite side of this document is being provided for your use and should be posted in compliance with the above section of the law. Note that the language in the warning was included in the legislation and should not be altered. The law also requires that the warning be in "22-point font" or larger.